

AQUA MIX® STONE ENHANCER

1. Product Name

Aqua Mix® Stone Enhancer

2. Manufacturer

Custom Building Products
 13001 Seal Beach Blvd.
 Seal Beach, CA 90740-2757
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3. Product Description

Aqua Mix Stone Enhancer is a no-sheen, enhanced-look, penetrating sealer formulated to darken and highlight the character and beauty of unsealed natural stone. It rejuvenates the color and improves the appearance of worn and weathered stone. May also be used as a pre-grouting sealer. Allows moisture-vapor transmission. It also effectively seals and darkens the color of grout joints.

KEY FEATURES

- Darkens and highlights
- Excellent stain protection
- No-sheen, enhanced look

AREAS OF USE

- Unsealed natural stone such as honed or textured marble, granite, slate, limestone, travertine, quartzite, and sandstone
- Effective for interior and exterior applications

LIMITATIONS

- Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable
- Sealers and finishes should not be used before or after use of Stone Enhancer
- If Stone Enhancer is not WIPED COMPLETELY DRY within 5 minutes, a residue may form
- If residue occurs, use a scrub brush or floor machine with Aqua Mix Heavy Duty Tile & Grout Cleaner or Stone Deep Clean to remove. Always try a small test area to ensure results. If results are not satisfactory, call technical services for additional options
- Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents
- Routine pressure-washing will affect expected wear
- Sealer will not prevent surface wear or etching from acids or caustic chemicals



EXPECTED WEAR UP TO 5 YEARS

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Expect more frequent application on exterior areas
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear

4. Technical Data

TEST METHOD	TEST RESULTS
CTI-072 Stain Resistance	Very Good
UV Resistance	Very Good

5. Installation

METHODS

Application

Read entire label before using. For new installations, sealer can be applied as soon as 48 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings. Apply using a sponge, brush, paint pad, cotton towel, or sprayer. NOTE: Be sure to completely wipe surface DRY within 5 minutes of each application using clean dry paper towels or cotton towels. If non-polished surfaces are left shiny after application, surfaces must be wiped dry as this indicates surface residue remains. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. Remove surface residue after each application. Ready for surface traffic in 12 hours after final coat. Keep dry for 12 hours. Achieves full cure in 48 hours. Some highly porous surfaces may require an additional coat after full cure. Clean applicator tools with mineral spirits after each use.



For Pre-Grouting Application

Apply over clean stone or tile a minimum of 4 hours prior to grouting - follow application procedures above.

Coverage

Approximately 500 to 1,500 sq. ft. (46 m² to 139 m²) per coat per gallon (3.8 L), depending on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

Handling and Storage

- Close container tightly after each use.
- Store in original container only. Store and use in temperatures between 40 °F - 90 °F (4 °C - 32 °C).
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

CAUTION

FLAMMABLE. MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. INFLAMMABLE. Keep away from heat and sources of ignition. Wear skin and eye protection. Do not breathe vapor or spray. Contains petroleum distillates and alkytrimalkoxy silanes. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

6. Availability & Cost

Contact the manufacturer or visit custombuildingproducts.com for information about product cost and availability.

	ITEM CODE	SIZE	PACKAGE
USA	030141	1 Pt. (473 ml)	Bottle
USA	030142-4	1 Qt. (946 ml)	Bottle
USA	030143	1 Gal. (3.8 L)	Bottle
USA	030144*	5 Gal. (19 L)	Pail
Canada	C030141	1 Pt. (473 ml)	Bottle
Canada	C030142-4	1 Qt. (946 ml)	Bottle
Canada	C030143	1 Gal. (3.8 L)	Bottle

*Indicates a special order item.

7. Limited Product Warranty

Custom Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom’s sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom’s printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

For details and complete warranty information, visit custombuildingproducts.com

8. Maintenance

Aqua Mix Concentrated Stone & Tile Cleaner, AquaKleen™ or AquaShield™ is recommended for routine spray and wipe cleaning and resealing.

9. Technical Services

For technical assistance contact Custom Building Products or visit custombuildingproducts.com.

10. Filing Systems

Additional product information is available from the manufacturer upon request.

Related Products:

- Aqua Mix
- Concentrated Stone & Tile Cleaner
- AquaKleen™
- AquaShield™

