

TEC™

The next generation in grout performance.

AccuColor XT™ grout is the next generation in cement-based grout performance. With its built-in resistance to staining, cracking, mold and mildew, AccuColor XT grout takes the abuse of everyday life to simplify maintenance and help keep your surface looking great.

Grout that stands up to life.

AccuColor XT Grout™

COLOR SELECTION CHART



Hammer it with kids. Pets. Feet. Food. Spills. AccuColor XT™ grout stands up to the challenge.



AccuColor XT grout takes life's everyday abuse and still complements the beauty of your tile surface. It provides accurate and consistent color across the installation and resists cracking, staining, mold and mildew*.

So go ahead. Live a little.

TEC™

SPECIALTY CONSTRUCTION BRANDS, INC.
1105 South Frontenac Street | Aurora, IL 60504-6451 U.S.A.
www.tecspecialty.com

©2007 TEC Specialty Products, Inc. Printed in the U.S.A. Form #ACXTGCR0507
TEC®, AccuColor XT™ and Everyday™ are trademarks of Specialty Construction Brands, Inc.

*Mold and mildew resistance is in the grout.

Color accurate.

Manufactured under strict color standards, AccuColor XT™ grout is chemically controlled during the curing process to ensure accurate, consistent color across the entire installation.

Resists staining.

Unique stain-blocking technology gives AccuColor XT grout built-in stain resistance. Most common household spills can't penetrate deep into the grout, allowing them to be removed from the surface. Because the stain inhibitors are built right into the grout, the stain resistance never wears away. AccuColor XT grout's stain inhibitors also reduce dirt pick-up, making it easier to maintain.

Resists mold and mildew.

The special antimicrobial additives in AccuColor XT grout protect it from mold and mildew growth, simplifying grout maintenance in wet areas. AccuColor XT grout's mold and mildew inhibitors undergo stringent tests for effectiveness.

Resists cracking.

The unique micro-structure gives AccuColor XT grout extreme durability. It's formulated for superior wear resistance and warranted against grout cracking when used as part of a TEC® brand crack-isolation system. See limited warranty for details.

Exceptionally easy to use.

With its smooth, creamy texture, AccuColor XT grout is easy to apply and offers easy clean-up characteristics.



Ask your sales associate or see tecspecialty.com for a copy of our limited warranties that apply to your installation of AccuColor XT grout.

- Exceeds ANSI A118.7 specifications
- Ideal for all types of ceramic and natural stone tile installations
- Excellent performance in high-traffic, exterior, and both wet and dry applications, including floors, walls, countertops, pools and fountains

Caring for your tile and grout surface

Tile and stone surfaces add beauty and personality to your home. A few simple steps can help keep your tile and grout looking great for years to come.

1. Promptly clean up spills. Although AccuColor XT™ grout does not absorb most household spills, you will need to clean spills off of its surface and off your tile. Allow 7 days after grout installation for full stain-resistance properties to be achieved.
2. Clean routinely with a pH neutral cleaner, such as TEC® Everyday™ Stone and Tile Cleaner, to keep dirt, soap scum or other deposits from building up on the surface of your tile and grout. It is important to let the grout cure 10 days after installation before starting routine cleaning (such as mopping). However, spills and other materials can be cleaned off as they occur.
3. Dust or dry mop tile and stone surfaces regularly to keep dirt and other particles from scratching the surface.

Available in select colors: "S"=sanded "U"=unsanded

910 - S, U Bright White
931 - S, U Standard White
902 - S, U Ivory
906 - S, U Cornsilk
988 - S, U Pearl
903 - S, U Birch
940 - S, U Antique White
991 - S Parchment
984 - S, U Almond
961 - S, U Sandstone Beige

Peel here.

Colors shown are reproductions and may vary from actual product.

915 - S, U Light Smoke
945 - S, U Light Buff
944 - S Light Chocolate
982 - S Summer Wheat
969 - S Coffee
933 - S Standard Gray
949 - S, U Silverado
927 - S Light Pewter
929 - S Charcoal Gray
941 - S, U Raven

Peel here.

AccuColor XT™ Sanded Grout (TA-585)

For grouting tile joints 1/8" to 1/2" (3 mm - 12 mm) wide.

Tile Size	Approximate Coverage per Pound (in Square Feet)			
	Joint Width			
	1/8" (3 mm)	1/4" (6 mm)	3/8" (9 mm)	1/2" (12 mm)
1" x 1" x 1/4"	2.04			
2" x 2" x 1/4"	3.83			
4" x 4" x 1/4"	7.28	3.64	2.43	1.82
4" x 8" x 1/4"	9.72	4.86	3.24	2.43
6" x 6" x 1/4"	10.92	5.47	3.64	2.73
8" x 8" x 1/4"	14.58	7.28	4.86	3.64
8" x 8" x 5/16"	11.11	5.88	3.85	2.94
10" x 10" x 3/8"	12.13	6.07	4.05	3.04
12" x 12" x 3/8"	14.57	7.28	4.86	3.64
16" x 16" x 3/8"	19.41	9.72	6.48	4.86
18" x 18" x 3/8"	21.83	10.93	7.28	5.46
24" x 24" x 1/2"	21.83	10.93	7.28	5.46


Tile Size	Approximate Coverage per Kilogram (in Square Meters)			
	Joint Width			
	1/16"	1/8"	1.5 mm	3 mm
25 x 25 x 6 mm	0.42			
50 x 50 x 6 mm	0.78			
100 x 100 x 6 mm	1.49	0.75	0.50	0.37
100 x 200 x 6 mm	1.99	1.00	0.66	0.50
150 x 150 x 6 mm	2.24	1.12	0.75	0.56
200 x 200 x 6 mm	2.99	1.49	1.00	0.75
200 x 200 x 8 mm	2.28	1.21	0.79	0.60
250 x 250 x 9 mm	2.48	1.24	0.83	0.62
300 x 300 x 9 mm	2.98	1.49	1.00	0.75
400 x 400 x 9 mm	3.98	1.99	1.33	1.00
450 x 450 x 9 mm	4.47	2.24	1.49	1.12
600 x 600 x 12 mm	4.47	2.24	1.49	1.12

AccuColor XT™ Unsanded Grout (TA-525)

For grouting tile joints up to 1/8" (3 mm) wide.

Tile Size	Approximate Coverage				
	per Pound (in Square Feet)		per Kilogram (in Square Meters)		
	Joint Width		Joint Width		
	1/16"	1/8"	1.5 mm	3 mm	
3/8" x 3/8" x 1/4"	1.67	0.83	10 x 10 x 6 mm	0.34	0.17
1" x 1" x 1/4"	4.45	2.23	25 x 25 x 6 mm	0.91	0.46
2" x 2" x 1/4"	8.90	4.45	50 x 50 x 6 mm	1.82	0.91
4 1/4" x 4 1/4" x 1/4"	18.90	9.44	108 x 108 x 6 mm	3.87	1.93
6" x 6" x 1/4"	26.67	13.33	150 x 150 x 6 mm	5.46	2.73
6" x 8" x 1/4"	30.49	15.24	150 x 200 x 6 mm	6.25	3.12
8" x 10" x 1/4"	39.53	19.76	200 x 250 x 6 mm	8.10	4.05
12" x 12" x 3/8"	35.56	17.78	300 x 300 x 10 mm	7.28	3.64
16" x 16" x 3/8"	47.50	23.70	400 x 400 x 10 mm	9.73	4.85
24" x 24" x 3/8"	71.00	35.50	600 x 600 x 10 mm	14.54	7.27

Choose the grout color to achieve the effect you want.



Looking for a grid effect to emphasize and frame each tile? Go with a contrasting grout color. For a subtle, blended background effect, closely match grout and tile colors, or add more depth with a slightly contrasting grout. TEC AccuColor XT grouts are formulated to help ensure consistent color under variable environmental conditions.